Installation instructions for Nelson-Rigg® Tank Bags CL-130 & CL-135, SLR-15, 25, SPRT-10

Read instructions carefully before installation. Diagrams show typical installation, your motorcycle may be different, use diagrams as a guide.
Make sure your motorcycle is clean and free from dirt, road grime etc. where the Nelson-Rigg® luggage mounts.



Using Strap 'A' with 2 male buckles on either end, connect one side to a female buckle on the front of tank bag. Loop opposite side around the frame or steering head behind the triple clamp making sure the strap is not pinched by the steering stops or displacing control cable or hoses. Adjust the strap length so the clips lay on the front of the fuel tank just behind the triple clamp. Clip remaining male buckle into open female buckle on tank bag.



Using Strap 'B' remove or raise the seat of your bike and either pass one of the buckles around the frame tubes or rear fuel tank or pass the loop in the middle of strap 'B' around the frame tubes or rear fuel tank and feed one of the male buckle through the loop securing the strap to your bike. Avoid sharp edges that may damage the nylon strap when it is tight.

* SPRT-10 uses a single strap for the rear



Now fasten the male buckles on both strap 'A' & 'B' into the female buckles on the tank bag and adjust to fit snug. When seated on the motorcycle, make sure you can freely operate all the controls with the tank bag in place.





Optional *MAG-MT-10* magnetic mounting kit converts this bag into a magnetic tank bag. Simply connect our 4 lightweight but powerful magnets into the female buckles on bag flaps and adjust to fit the contours of your tank.





Optional *TLPK-MT-20* tail pack mounting kit converts this bag into a versatile tail pack. Simply connect the 4 webbing straps into the female buckles on bag flaps and attach the nylon hooks to a solid part of your bike.





Optional *SUC-MT-50* suction cup mounting kit converts this bag into a tank bag able to securely mount to any painted surface. Simply connect our 4 powerful suction cups into the female buckles on bag flaps and adjust to fit the contours of your tank.

Warning:

Read the installation instructions and make yourself familiar with the process of installing the Nelson-Rigg® product(s) on your bike. It is your responsibility to mount the product correctly and securely as outlined in these instructions. Nelson-Rigg® products are intended for use at USA street legal speeds as posted by the individual States. Nelson-Rigg® luggage must not be overloaded. Max carrying capacity is 10 lbs per bag or the maximum load suggested by the manufacturer of the vehicle, whichever is less.
Failure to adhere to these warnings may result in, but not be limited to: the luggage becoming detached, the product becoming tangled in moving parts of the vehicle, unstable vehicle dynamics, reduction in the ability to control the vehicle. The result(s) of could lead to serious injury.

Always ride safely, adhering to the local highway regulations. Always wear a helmet and protective apparel.

it's not just a bike®

www.nelsonrigg.com

Nelson-Rigg USA, Inc. 3518-A Lake Center Drive, Santa Ana, CA 92704 • 714.850.1811 • fax 714.850.1848

All Nelson-Rigg products are made to the highest standards of quality and finish, providing unequalled strength, durability and function. Our accessories are warranted to be free from defects in materials and workmanship during the specified warranty period and applies only to the original purchaser of the product with the **original sales receipt**. To obtain warranty service, you must contact Nelson-Rigg at (714) 850-1811 or via e-mail at info@nelsonrigg.com to obtain a return authorization number. Visit our website or contact us for more info on our warranty and procedures.

Please complete the warranty form below or register at (https://www.nelsonrigg.com/store/warranty.aspx) to activate your warranty within 30-days from date of purchase. All items returned for warranty evaluation must still be accompanied with a copy of the original proof of purchase. During the warranty period Nelson-Rigg, at our discretion will repair or replace the product if it becomes defective, malfunctions or otherwise fails to confirm to this warranty and return it to you free of charge (within USA only).